

## WHAT IS CLAIMED IS:

- Sub C1
1. An apparatus capable of image capturing comprising:
- an imaging device which captures image data;
  - a recorder for recording image data transferred from said imaging device into a specified medium;
  - a display unit for displaying the image data transferred from said imaging device;
  - an exposure controller for controlling exposure in capturing an image by means of said imaging device; and
  - a changer for changing exposure control by said exposure controller between recording by a recorder and displaying by a display unit.
2. An apparatus capable of image capturing as claimed in claim 1, wherein said exposure controller controls the exposure by changing an aperture stop.
3. An apparatus capable of image capturing as claimed in claim 2, wherein said exposure controller sets the aperture stop larger in the displaying stage than in the recording stage.
4. An apparatus capable of image capturing as claimed in claim 1, wherein said exposure controller controls exposure by changing a shutter speed.

09100799-061998

5. An apparatus capable of image capturing as claimed in claim 4, wherein said shutter speed at the time of capturing an image for display use is set slower than a shutter speed at the time of capturing an image for recording use when a subject has a luminance lower than a specified luminance.

6. An apparatus capable of image capturing as claimed in claim 4, wherein said shutter speed at the time of capturing an image for display use is set faster than a shutter speed at the time of capturing an image for recording use when a subject has a luminance lower than a specified luminance.

7. An apparatus capable of image capturing as claimed in claim 2, wherein a gamma correcting portion for correcting a gradation characteristic of an image is provided and said changer changes the gradation characteristic between recording and displaying.

8. An apparatus capable of image capturing as claimed in claim 7, wherein said gamma correcting portion sets a gradation characteristic corresponding to the type of an image output destination.

9. An apparatus capable of image capturing as claimed in claim 8, wherein the image output destination is a built-in

09100799-061998

monitor unit or an external monitor unit. .

10. An apparatus capable of image capturing comprising:

- an imaging device which captures image data;
- a recorder for recording image data transferred from said imaging device into a specified medium;
- a display unit for displaying the image data transferred from said imaging device;
- an interpolating portion for executing interpolation of pixels constituting an image; and
- a changer for changing an interpolating process by said interpolating portion between recording by a recorder and displaying by a display unit.

11. An apparatus capable of image capturing as claimed in claim 10, wherein said changer executes in the displaying stage an interpolating process of a faster processing speed than in the recording stage.

12. An apparatus capable of image capturing as claimed in claim 10, wherein a gamma correcting portion for correcting a gradation characteristic of an image is provided and said changer can change the gradation characteristic between recording and displaying.

09100799-061998

13. An apparatus capable of image capturing as claimed in claim 12, wherein said gamma correcting portion sets a gradation characteristic according to the type of an image output destination.

14. An apparatus capable of image capturing as claimed in claim 13, wherein the image output destination is a built-in monitor unit or an external monitor unit.

15. An apparatus capable of image capturing as claimed in claim 10, wherein said interpolating portion executes an interpolating process based on data of each color of the image data.

16. An apparatus capable of image capturing comprising:

- an imaging device which captures image data;
- an image recording mode setting portion capable of setting an image recording mode;
- a band correcting portion for correcting a frequency characteristic of image data transferred from the imaging device;
- a gamma correcting portion for correcting a gradation characteristic of the image data transferred from the imaging device; and
- a controller for controlling the band correcting

866T90"562001550

portion and the gamma correcting portion according to the set image recording mode.

17. An apparatus capable of image capturing as claimed in claim 16, wherein said band correcting portion has a plurality of frequency characteristics.

18. An apparatus capable of image capturing as claimed in claim 16, wherein said gamma correcting portion has a plurality of gradation characteristics.

19. An apparatus capable of image capturing as claimed in claim 16, wherein said image-recording mode setting portion sets a size of an image to be recorded.

20. An apparatus capable of image capturing as claimed in claim 19, wherein said controller controls the band correcting portion so as to emphasize an intermediate-frequency component of frequency components included in the image as the image size set by the image recording mode setting portion decreases.

21. An apparatus capable of image capturing as claimed in claim 19, wherein said controller controls the gamma correcting portion so as to emphasize a contrast of the image as the image size set by the image recording mode setting

09100799 061998  
866790 6620150

portion decreases.

22. An apparatus capable of image capturing as claimed in claim 16, wherein said image-recording mode setting portion sets the compression rate in a recording stage.

23. An apparatus capable of image capturing as claimed in claim 22, wherein said controller controls the band correcting portion so as to suppress a high-frequency component of frequency components included in the image as the compression rate set by the image recording mode setting portion increases.

24. An apparatus capable of image capturing as claimed in claim 22, wherein said controller controls the gamma correcting portion so as to emphasize a contrast of the image as the compression rate set by the image recording mode setting portion increases.

25. An apparatus capable of image capturing as claimed in claim 16, wherein said image-recording mode setting portion has a mode in which a halftone image is recorded as a mode to be set.

26. An apparatus capable of image capturing as claimed in claim 25, wherein said controller controls the band

09100799-061998

correcting portion so as to emphasize an intermediate-frequency component of frequency components included in the image when the mode in which a halftone image is recorded is set in the image recording mode setting portion.

27. An apparatus capable of image capturing as claimed in claim 26, wherein said controller controls the band correcting portion so as to further suppress high-frequency component of the frequency components included in the image.

28. An apparatus capable of image capturing as claimed in claim 25, wherein said controller controls the band correcting portion so as to suppress a high-frequency component of the frequency components included in the image when the mode in which a halftone image is recorded is set in the image recording mode setting portion.

29. An apparatus capable of image capturing as claimed in claim 25, wherein said controller controls the gamma correcting portion so as to emphasize a contrast of the image further than a specified reference gradation characteristic when the mode in which a halftone image is recorded is set in the image recording mode setting portion.

30. An apparatus capable of image capturing as claimed in claim 16, wherein said image-recording mode setting portion

09100799-061998

has a mode in which a binary image is recorded as a mode to be set.

31. An apparatus capable of image capturing as claimed in claim 30, wherein said controller controls the band correcting portion so as to emphasize an intermediate-frequency component of frequency components included in the image when the mode in which a binary image is recorded is set in the image recording mode setting portion.

32. An apparatus capable of image capturing as claimed in claim 30, wherein said controller controls the gamma correcting portion so as to emphasize a contrast of the image further than a specified reference gradation characteristic when the mode in which a binary image is recorded is set in the image recording mode setting portion.

33. An apparatus capable of image capturing comprising:

an imaging device having a filter array of a plurality of colors;

a compression rate setting portion for setting a compression rate of image data;

an interpolating portion for executing pixel interpolation based on data of colors constituting image data; and

05100799.051999



a controller for controlling the interpolating portion according to a compression rate set by said compression rate setting portion.

34. An apparatus capable of image capturing as claimed in claim 33, wherein an image size setting portion for setting an image size is provided and said controller controls the interpolating portion according to the image size set by the image size setting portion.

35. An apparatus capable of image capturing as claimed in claim 33, wherein an interpolating process that executed in said interpolating portion is selected out from among an interpolating process employing an average filter, an interpolating process employing a median filter and an interpolating process for executing simple interpolation with adjacent pixel data.

36. An apparatus capable of image capturing as claimed in claim 33, wherein an interpolating process of a higher processing speed is executed as the compression rate set by the compression rate setting portion is higher.

37. An image data processing method for an apparatus capable of image capturing, comprising the steps of:  
setting an compression rate of image data obtained

09100799-051998

from an imaging device; and

executing an interpolating process on image data of colors constituting the image data according to the set compression rate.

38. An image data processing method as claimed in claim 37, wherein an interpolating process of a higher processing speed is executed in the apparatus capable of image capturing as the set compression rate becomes higher in interpolating process control.

39. An image data processing method for an apparatus capable of image capturing which can display and record a captured image, comprising the steps of:

capturing image data by means of an imaging device;

and

executing a varied interpolating process depending on whether the captured image is to be displaced or recorded.

40. An image data processing method as claimed in claim 39, wherein an interpolating process of a faster processing speed is used in displaying the image than the interpolating process in recording the image during said interpolating process control.

41. An image data processing method as claimed in claim

09100799-061998  
866T90-66200T60

39, further comprising a gamma correcting step for correcting a gradation characteristic of an image.

09100799 "061998  
866T90" 66700760